

Waldrich Coburg

PMC 4500-F20 • Serial No. 3.8504




Performance



- | | |
|-------------------------------|-------------|
| ✓ Spindle Power | 120 kW |
| ✓ Spindle Speed (Gear rate 1) | 5-250 rpm |
| ✓ Spindle Speed (Gear rate 2) | 20-1000 rpm |

Range on Axes



- | | | |
|---------------------------|--------|-----------|
| ✓ Table 1 & 2 | X-Axis | 13.125 mm |
| ✓ Coupled tables | X-Axis | 27.000 mm |
| ✓ Milling Carriage | Y-Axis | 7.480 mm |
| ✓ Milling Carriage Stroke | Z-Axis | 1.500 mm |
| ✓ Crossbar | W-Axis | 3.550 mm |



Waldrich Coburg PMC 4500 – F20

Further technical information

Main dimensions

✓ Clearance between covers of portal columns	4.550 mm
✓ Clearance between floor plate / table and spindle	4.750 mm
✓ Setup width	3.500 mm
✓ Setup length table 1 & 2	12.500 mm
✓ Setup length (coupled tables)	26.250 mm

Travel speeds

✓ Machine portal (X-Axis)	15.000 mm/min
✓ Milling Carriage (Y-Axis)	15.000 mm/min
✓ Milling Carriage Stroke (Z-Axis)	10.000 mm/min
✓ Crossbar (W-Axis)	5.000 mm/min

Automatic Tool Changer

✓ Storage (quantity)	140 tool stations
✓ ISO 50 Station	124
✓ ISO 60 Station	15
✓ Adapter ISO60/50	1

Automatic Attachment Changer

✓ Magazine capacity	17 attachment stations
✓ Spindle Units	9 stations
✓ Spindle cover	1 station
✓ Heavy tools	3 stations
✓ Travel speed	30.000 mm/min

You are interested? Contact Us!

Tel.: +49 (0) 2237 9292-30
Mail: yk@klueppelberg.de
Web: <https://klueppelberg.de>

